

In the Claims

Please cancel claim 3.

Please add new claims 30 - 32.

Please substitute the following amended claims 1,2,4,9,26, and 29 for those currently pending.

B1 1. (currently amended) A method of providing information at the point of use of a window assembly comprising the steps of:

providing masking material comprising a substrate and an adhesive disposed over a first face of the substrate;

~~applying at least one strip of masking material to a surface of a pane of the window assembly; and~~

pre-printing information on a second face of the substrate of the ~~at least one strip of~~ masking material; and

forming a protective covering comprising the masking material on a surface of a pane, the protective covering being sized and positioned so that an unmasked apron of the surface extends between an outer periphery of the protective covering and an outer periphery of the pane;

the unmasked apron being large to receive a sash yet small enough that the protective covering protects a portion of the pane not covered by the sash.

2. (currently amended) The method of claim 1, wherein the step of pre-printing information on the second face of the substrate of the at least one strip of masking material occurs before the step of ~~applying the at least one strip of masking material to the surface of the pane~~ forming the protective covering.

3. (canceled)

B1
cont 4. (currently amended) A method of providing information at the point of use of a window assembly comprising the steps of:

providing masking material comprising a substrate and a first adhesive disposed upon a first face of the substrate;

cont
Q1 applying ~~at least one strip of masking material to a surface of a pane of the window assembly;~~ and

forming a protective covering on a surface of a pane using the masking material, the protective covering being sized and positioned so that an unmasked apron of the surface extends between an outer periphery of the protective covering and an outer periphery of the pane;

the unmasked apron being large enough to receive a sash yet small enough that the protective covering protects a portion of the pane not covered by the sash; and

applying an information bearing sheet over the ~~at least one strip of masking material~~
protective covering.

5. (original) The method of claim 4, wherein the information bearing sheet comprises a sheetstock and a second adhesive disposed upon a first face of the sheetstock.

6. (original) The method of claim 5, wherein the second adhesive has substantially greater adhesion than the first adhesive.

7. (original) The method of claim 5, wherein the sheetstock comprises a substantially frangible material.

8. (original) The method of claim 5, wherein the sheetstock comprises paper.

9. (currently amended) A window assembly, comprising:
an insulating glass unit including a first pane having a first surface;
a protective covering disposed over a masked portion of the first surface of the first pane;

✓ the protective covering comprising a plurality of strips disposed across the first surface of the first pane; and

~~the first surface of the first pane having an unmasked apron extending between an outer periphery of the protective covering and an outer periphery of the first pane;~~

the protective covering being sized and positioned so that an unmasked apron of the first surface extends between an outer periphery of the protective covering and an outer periphery of the pane, the unmasked apron being large enough to receive a sash yet small enough that the protective covering protects a portion of the pane not covered by the sash.

✓ 10. (original) The window assembly of claim 9, wherein the plurality of strips are disposed in a sequentially overlapping fashion with each subsequent strip overlapping a portion of a preceding strip so that the protective covering can be easily removed one strip at a time.

B1 cont. 11. (original) The window assembly of claim 10, wherein the plurality of strips comprises a second strip partially overlapping a first strip, and a third strip partially overlapping the second strip.

12. (original) The window assembly of claim 10, wherein the plurality of strips comprises n strips with the nth strip partially overlapping an (n-1) strip of the plurality of protective strips.

✓ 13. (original) The window assembly of claim 12, wherein the nth strip includes indicia for indicating that the nth strip should be the first one removed.

14. (original) The window assembly of claim 9, further including an information bearing sheet overlaying the protective covering.

15. (original) The window assembly of claim 14, wherein the information bearing sheet comprises a sheetstock having a first side and a second side.

Don't 16. (original) The window assembly of claim 14, wherein the information bearing sheet includes second indicia printed on a second side thereof.

17. (original) The window assembly of claim 14, wherein the information bearing sheet includes first indicia printed on a first side thereof.

18. (original) The window assembly of claim 17, wherein the information bearing sheet includes a second adhesive overlaying the first indicia and the first side of the sheetstock.

cont. ✓ 19. (original) The window assembly of claim 18, wherein the second adhesive has substantially greater adhesion than the first adhesive.

20. (original) The window assembly of claim 18, wherein the second adhesive and the protective covering are both substantially transparent to allow viewing of the first indicia therethrough.

✓ 21. (original) The window assembly of claim 18, wherein the second adhesive and the protective covering are both substantially translucent.

✓ 22. (original) The window assembly of claim 14, wherein the information bearing sheet includes indicia comprising an advertisement for goods likely to be purchased by a user of the window assembly.

✓ 23. (original) The window assembly of claim 14, wherein the information bearing sheet includes indicia comprising a National Fenestration Rating Council rating for the window assembly.

24. (original) The window assembly of claim 9, wherein each strip of the protective covering includes a tab portion.

✓ 25. (original) The window assembly of claim 24, wherein each strip of the protective covering comprises a substrate and an adhesive disposed over a first face of the substrate, and the tab portion of each strip comprises a first portion of the substrate folded so as to overlap a

B
cont second portion of the substrate so that the adhesive overlaying the first portion is adhered to the adhesive overlaying the second portion.

26. (currently amended) A method of protecting a masked area of a planar surface comprising the steps of:

providing masking material having a width;

providing the width of the masking material to a masking calculator;

providing a desired width of the masked area to the masking calculator;

cont.
ai ~~instructing the masking calculator to determine an optimal number of strips;~~

~~instructing the masking calculator to calculate an overlap dimension; and~~

~~applying the optimal number of strips to the planar surface in an overlapping fashion~~

according to the overlap dimension;

calculating a number of strips and an overlap dimension for forming a protective covering

sized so that an unmasked apron of the first surface surrounds the protective covering; and

applying a plurality of strips to the surface in an overlapping fashion according to the overlap dimension.

✓ 27. (original) The method of claim 26, wherein the strips are applied in a sequential fashion with each subsequent strip partially overlapping a preceding strip by the overlap dimension.

28. (original) The method of claim 26, wherein the step of providing the desired width of the masked area to the masking calculator includes the step of detecting a dimension of the planar surface.

29. (currently amended) A method of providing information at the point of use of a window assembly comprising the steps of:

applying a protective covering to a pane of the window assembly, the protective covering being sized and positioned so that an unmasked apron of the pane surrounds the protective covering;

providing information related to the window assembly;

printing the information on a sheet;

attaching the information bearing sheet to the ~~window assembly~~ protective covering; and

transporting the information bearing sheet and the window assembly to a point of use.

30. (new) The method of claim 29, wherein the unmasked apron is large enough to receive a sash yet small enough that the protective covering protects a portion of the pane not covered by the sash.

31. (new) The method of claim 29, wherein the window assembly comprises an insulating glass unit.

32. (new) The method of claim 26, wherein the unmasked apron is large enough to receive a sash yet small enough that the protective covering protects a portion of the pane not covered by the sash.